

ArcticStar 55 *Ultimate Versatility*

Featuring a hot water boost button, the 55 can raise the temperature of your water to up to 95C. This cooler comes with an integrated cup holder as standard, but this can be removed depending on preference. Further upgrade this cooler by adding a SIP Neo3 device which automatically sanitises the cooler.

- 17cm dispense height
- Dispenses ambient, 20ltrs/h chilled, and 9ltrs/h hot
- Safety lock feature for hot water
- Integrated cup dispenser on lower front panel



Accessories

Installation Rail & Filter

Includes compression fitting, 1-micron green filter, water block, copper pressure reducing valve & non-return valve.



Sip Neo3

An automatic sanitising device compatible with floor standing, tank fed POU coolers. Reduces sanitising visits and saves your customers money on electricity.



Overflow Kit

We have a selection of drip tray overflow kits that are available for pre or self-installation. Our 10ltr kit (pictured) features an alarm which sounds when the container is full.



Mains Drainage

Connect the drip tray to mains drainage to easily dispose of waste water. Requires modification of the drip tray and bracket and is only available factory installed.




Pumped Waste

Pumps waste water directly into the mains drainage point, even against gravity and over a distance of 100m. Only available factory installed.



Conversion Kits

Easily convert your 3300X cooler to bottled or POU to suit your customers preference. We offer conversion kits for AA coolers for full control of your offering.



Cowling

Metal cowling to fix floor standing water coolers to the wall. Keeps machines secure and safe from tampering. Comes in anthracite grey.



Speak with an expert

We're here to answer all your questions.

Express Water Coolers

+44 (0) 1925 919 828

expresswatercoolers.co.uk

sales@expresswatercoolers.co.uk



**EXPRESS
WATER COOLERS**

Description	Code	Dimensions H x W x D (mm)	Approx. Weight
Bottled Floor Standing AC / HC	WCBC55 / WCBH55	1160 x 340 x 350	18kg
Bottled Table Top AC / HC	WCBTC55 / WCBTH55	480 x 340 x 350	15kg
POU Floor Standing AC / HC	WCPC55 / WCPH55	1140 x 340 x 350	18kg
POU Table Top AC / HC	WCPTC55 / WCPH55	460 x 340 x 350	15kg