

borg &
overström

b1



An all-round exclusive

The strength of this range lies in its locational flexibility and sleek, considered design which maintains the consistency that Borg & Overström upholds.



Power requirements

Hertz 50/Volts 220-240

Max power consumption

Chilled & Ambient 80W

Chilled & Hot 580W

Chilled temperature

Min 2°C/Max 11°C

Hot temperature

Max 90°C

Throughput litres per hour

Chilled 16/Hot 6

Dimensions

Floorstanding

Dispense height

WxDxH

260x485x1145mm

175mm

Key Features

- Rugged push-lever tap controls
- Integrated cup dispenser
- Available as POU or bottled
- Chilled, ambient and hot

Available accessories

- b1 Wall Bracket Set
- Sanitisation Kit
- Install Kit with Filter
- Blue Tint Cups



Water options



Chilled




Ambient



Hot

Configuration



Floorstanding

Recommended environment



Offices



Hospitality



Healthcare



Education



Leisure

Number of users



6–10



11–25

b1 Models

Reservoir, POU, Floorstanding, Chilled, Ambient—401550

Reservoir, POU, Floorstanding, Chilled, Hot—401560


Reservoir, Bottled, Floorstanding, Chilled, Ambient—401750

Reservoir, Bottled, Floorstanding, Chilled, Hot—401760

Water system



Bottled



Reservoir

Phone
+44 (0)1362 695 006
Email
sales@borgandoverstrom.com

borgandoverstrom.com

Distributed by

Ref: 838131
Version: 13012015