# borg& overström







## borg& overström

Evolutionary excellence Built on the reliable foundation laid by the B2, the B3 boasts additional features such as a highcapacity dispense area, integrated cup dispenser and the option of sparkling water.

Reasons to choose

- Ultra-hygienic touch sensitive control panel
- High-capacity dispense area for bottles and jugs
- Integrated cup dispenser
- Sealed, hygienic, direct-chill cooling system
- Sparkling water option





Beautifully refreshing.

b3










Configuration

Countertop









Beautifully refreshing.

### Available colours









### Borg & Overström Totality



Driven by a relentless pursuit of excellence, Borg & Overström Totality" is a research and development methodology for the advancement of hygiene, innovation and technology in refreshment systems.



Ultra-violet sterilising system For added hygiene confidence, appliances can be fitted with Viovandt<sup>w</sup> – an ultra-violet sterilisation process that reduces water-born bacteria.



World-class filtration For the ultimate drinking experience, Borg & Overström appliances can be pre-fitted with a 3M filter to reduce sediment, chlorine, odours and scale. Beautifully refreshing.



Laboratory certified 99.999% bacteria-free Every Borg & Overström appliance undergoes an anti-microbial, antipathogen, sanitising procedure. The reassurance of hygienically safe appliances is provided by the unique bacteria-eliminating process, Sterizen<sup>™</sup>.



Biofilm, limescale and impact resistant epoxy resin panel finish Providing an increased level of hygiene and longevity, Fyni™ is a scratch and impact resistant epoxy-resin surface finish - effectively resisting biofilm development and limescale cohesion.

b3



## borg& overström

B3 Models	Silver	White	Black
Direct Chill, Countertop			
Chilled, Ambient	104001	104002	104003
Chilled, Hot, Ambient	104011	104012	104013
Direct Chill, Floorstanding			
Chilled, Ambient	104021	104022	104023
Chilled, Hot, Ambient	104031	104032	104033
Chilled, Hot, Sparkling	104041	104042	104043
Chilled, Ambient, Sparkling	104051	104052	104053

Power requirements Hertz 50/Volts 220-240 Max power consumption Chilled & Ambient 100W Chilled & Hot 550W Chilled, Ambient & Hot 550W Chilled, Hot & Sparkling 640W Chilled, Ambient & Sparkling 140W

Chilled temperature Min 2°C/Max 11°C Hot temperature Max 92°C Throughput litres per hour Chilled 30/Hot 6 DimensionsWxDxHFloorstanding325x380x1065mmCountertop325x380x475mmDispense height265mm

EXPRESS WATER COOLERS



Beautifully

refreshing.



#### Additions for B3



Cup dispenser blanking panel Replacement top panel for situations where an integral cup disposable cups designed dispenser is not required.

Printed paper cups Environmentally-friendly to fit Borg & Overström cup dispensers perfectly.

Deep-sparkle CO<sup>2</sup> refills Can be disposed via standard steel recycling or general waste. Requires CO<sup>2</sup> regulator with gauge.

:O: E290 5 Nº C org& verströ

> Sanitisation kit Six monthly sanitising cycles ensure appliances function at the optimum hygiene levels.

Waste kit overflow sensor Featuring an audible highwater level alarm to prevent the waste tank from overflowing. Included as standard on floorstanding models.



Leak detection kit Featuring a moisture sensor that Install appliances simply and shuts the water supply in the unlikely event of a leak.

**EXPRESS** WATER COOLERS Install kit with 3M filter effectively in a wide range of applications. Complete with a 3M filter.

Ultra-violet filter kit Complete Viovandt<sup>™</sup> filter kit to assist in water purification and removal of unwanted micro-organisms.

Wall bracket kit For added security, use the wall bracket set to anchor your watercooler back to the wall. Simple to fit and unobtrusive.



wall and protects plumbing and electrical connections. Ideal for public areas.

Beautifully refreshing.

