

# WL3 Firewall®

Superior purification, proven performance and elegant design



## High quality water dispenser for the modern workplace

The WL3 Firewall (WL3 FW) by Waterlogic® brings a variety of refreshing purified water choices to the workplace. Supplying cold, sparkling, hot and extra hot options, and utilising Firewall, Waterlogic's industry leading UV purification technology.

## Advanced technology

The WL3 FW features three core technologies:



### High performance filtration

Waterlogic's filters are certified to stringent standards, carrying the Water Quality Association's (WQA) Gold Seal of approval, meaning they offer the best possible filtration. This guarantees each drop is as good as the last.



### Firewall

Waterlogic's patented and exclusive Firewall technology utilises a highly effective UVC purification system that acts at the point of dispense. Firewall guarantees up to 99.9999% bacteria water. Glass after glass.



### BioCote® protection

The WL3 FW key surfaces are infused with BioCote®, a silver ion additive able to inhibit microbial growth on the surface of the products helping to reduce unpleasant odours, degradation of key surfaces and the potential for cross contamination.

## High quality sparkling water system

WL3 FW is designed with a unique technology which delivers premium sparkling water. The system utilises draw-back sparkling water technology to ensure superior quality sparkling water time after time.

## Features

Firewall, patented UV technology reduces the risks of bacteria, viruses, and pathogens purifying the water up to 99.9999%, 100% of the time

Superior quality sparkling water, safely purified to NSF sanitation and food safety standard, such as NSF/ANSI 55 Class A and P231 for microbiological water purifiers

Touch sensitive control panel for easy operations

Environmentally friendly refrigeration using R600a: naturally occurring refrigerant gas with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)

LED UV fault indicators for straightforward fault diagnosis and servicing

BioCote® protected dispensing area (including nozzle, drip tray and dispensing buttons)

## Water options

	cold	sparkling	ambient	hot	extra hot
1					
2					
3					
4					

\*Countertop model not available in cold, hot, sparkling.

## Number of users

 up to 30

## Technical specifications

Types available  
Freestanding and countertop

Dimensions  
Freestanding: 385 mm (W) x 1150 mm\*(H) x 460 mm (D)  
Countertop: 385 mm (W) x 490 mm\*(H) x 460 mm (D)

Dispensing area height  
220 mm

Weight  
Countertop: 22-27 KG  
Freestanding: 30-34 KG

Standard filtration supplied  
Carbon block filter (CBC)

Storage capacity  
Hot tank (Countertop): 1.5 litres  
Hot tank (Freestanding): 2 litres  
Cold tank (Freestanding): 4 litres  
Cold tank (Countertop): 2 litres  
Sparkling tank: 1.8 litres

Compressor  
220/240v 50Hz

Water temperature settings  
Cold: 5°C  
Hot: 87°C  
Extra Hot: 93°C

\*Measurements include feet



## Tested and certified



\*certificate may vary depending on different models or products

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

## Speak to a Water Expert

We're here to answer all your questions.  
[sales@expresswatercoolers.co.uk](mailto:sales@expresswatercoolers.co.uk)  
+44 (0) 1925 919 828

Express Water Coolers  
Unit 24 Craven Court  
Winwick Quay, Warrington, Wa2 8QU  
[www.expresswatercoolers.co.uk](http://www.expresswatercoolers.co.uk)

