

WL100

Simple, straight forward functionality
without compromising on quality



R600a gas

**Zero
environmental
impact**

Easy to use point-of-use (POU) solution for perfectly chilled and hot water

A great value dispenser, supplying safe and refreshing drinking water for the workplace. The WL100 is the ideal solution for your basic hydration needs at a competitive price.

Advanced technology

The WL100 features two core technologies:



High performance filtration

Waterlogic's filters are certified to stringent standards, carrying the Water Quality Association's (WQA) Gold Seal of approval, meaning they offer the best possible filtration. This guarantees each drop is as good as the last.



BioCote® protection

The key plastic surfaces surrounding the dispensing area are infused with BioCote®, a silver ion additive that provides continuous antimicrobial protection against a broad spectrum of bacteria, mould and fungi, and reduces the risk of cross-contamination.

Waterlogic's promise

Waterlogic combines water science and the latest technologies available to offer safe, great tasting water, whilst preserving the health integrity of the workplace.

Features

Ergonomic design with simple buttons and icons for easy dispensing operation

Environmentally friendly refrigeration with R600a: natural occurring refrigerating gas with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)

Generous drip tray capacity to collect accidental spillage

BioCote® protected dispensing area (including drip tray body, cold faucet and dispensing buttons)

Robust and durable design, suitable for most workplace environments

Technical specifications

Types available
Freestanding and countertop

Dimensions
Freestanding: 345mm (W) x 1022mm (H) x 367mm (D)
Countertop: 345mm (W) x 450mm (H) x 367mm (D)

Dispense area height
220mm

Weight
Freestanding: 28 kg
Countertop: 23 kg

Standard filtration supplied
Carbon block filter (CBC)





Storage capacity
Cold tank: 2 litres
Hot tank: 1.5 litres

Drip tray capacity
1.5 litres

Compressor
220/240v 50Hz (R600a)

Water temperature settings
Cold: 5-8°C (default set at 5°C)
Hot: 85-90°C

Water options

	cold	sparkling	ambient	hot	extra hot
1					
2					

Number of users

 up to 20



Tested and certified



CE QUALITY & SAFETY
GUARANTEED

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Speak to a Water Expert

We're here to answer all your questions.
sales@expresswatercoolers.co.uk
+44 (0) 1925 919 828

Express Water Coolers
Unit 24 Craven Court
Winwick Quay, Warrington, Wa2 8QU
www.expresswatercoolers.co.uk

